

SmartLink SL-5ET on pienikokoinen muovikoteloitu 5-porttinen gigabitin Ethernet-kytkin, jotka on suunniteltu verkkoympäristöihin kuten kouluihin, kotitalouksiin ja pk-yrityksiin. Kytkimessä on 5 kpl 10/100/1000 Mbps nopeudeltaan mukautuvaa Ethernet-porttia. Laitteessa on 4 kV ylijännitesuojaus, joka tarjoaa vakaata toimintaa sekä lisäturvaa. Auto MDI/MDIX -toiminto on myös tuettuna. Asetuksia ei tarvita; kytkin toimii heti, kun se kytketään virtaan ja kaapelit yhdistetään.



- 5x1000Mbps Ethernet port with auto-negotiation function
- Support 1000Mbps speed rate, MDI/MDIX
- Support IEEE802.3x Flow control and back pressure control
- Each port has the complete LED Indicator light
- Each port supports wire-speed switching , 64~1518 frame length can reach the wire speed
- Support 5-16VDC voltage input
- Support 4kV lightning protection of each port
- Require no configuration and will instantly operate as soon as you power it up

Specification

Model No.	SL-5ET
Certifications	CE, RoHS
Ethernet Port	<ul style="list-style-type: none"> ➤ Connector: RJ45 ➤ Data Rate: 10/100/1000Mbps ➤ Distance: 100m ➤ UTP Type: UTP-5e or higher level
Performance	<ul style="list-style-type: none"> ➤ Processing Type: Store and Forward ➤ Transmission Mode: half/full-duplex with auto-negotiation function ➤ MAC Table Size: 1k ➤ Buffer Space: 448k ➤ Back bandwidth: 10G ➤ Time Delay: <150μs
Power	<ul style="list-style-type: none"> ➤ Power type: external power supply ➤ Input Voltage: 100V~240VAC 50/60Hz ➤ Connector: DC Socket ➤ Working Voltage: 12V
Environment	<ul style="list-style-type: none"> ➤ Storage Temperature: -40~70°C ➤ Operating Temperature: -10~55°C ➤ Relative Humidity: 5-90% (no condensation)
Warranty	2 years
Physical Characteristics	<ul style="list-style-type: none"> ➤ Dimension: 93×53×23mm ➤ Weight: 0.2kg ➤ Color: Black

Maahantuonti ja tekninen tuki:

Microdata Finland Oy
Robert Huberin tie 2
01510 VANTAA

tuki@microdata.fi / +358 9 42474920