

**SmartLink SL-8ET** on pienikokoinen muovikoteloitu 8-porttinen gigabitin Ethernet-kytkin, jotka on suunniteltu verkkoympäristöihin kuten kouluihin, kotitalouksiin ja pk-yrityksiin. Kytkimessä on 8 kpl 10/100/1000 Mbps nopeudeltaan mukautuvaa Ethernet-porttia. Laitteessa on 4 kV ylijännitesuojaus, joka tarjoaa vakaata toimintaa sekä lisäturvaa. Auto MDI/MDIX -toiminto on myös tuettuna. Asetuksia ei tarvita; kytkin toimii heti, kun se kytketään virtaan ja kaapelit yhdistetään.



- 8x1000Mbps Ethernet port with auto-negotiation function
- Support 1000Mbps speed rate, MDI/MDIX
- Support IEEE802.3x Flow control and back pressure control
- Each port has the complete LED Indicator light
- Each port supports wire-speed switching , 64~1518 frame length can reach the wire speed
- Support 5-16VDC voltage input
- Support 4kV lightning protection of each port
- Require no configuration and will instantly operate as soon as you power it up

### Specification

Model No.	<b>SL-8ET</b>
Certifications	CE, RoHS
Ethernet Port	<ul style="list-style-type: none"> <li>➤ Connector: RJ45</li> <li>➤ Data Rate: 10/100/1000Mbps</li> <li>➤ Distance: 100m</li> <li>➤ UTP Type: UTP-5e or higher level</li> </ul>
Performance	<ul style="list-style-type: none"> <li>➤ Processing Type: Store and Forward</li> <li>➤ Transmission Mode: half/full-duplex with auto-negotiation function</li> <li>➤ MAC Table Size: 2k</li> <li>➤ Buffer Space: 448k</li> <li>➤ Back bandwidth: 16G</li> <li>➤ Time Delay: &lt;150µs</li> </ul>
Power	<ul style="list-style-type: none"> <li>➤ Power type: external power supply</li> <li>➤ Input Voltage: 100V~240VAC 50/60Hz</li> <li>➤ Connector: DC Socket</li> <li>➤ Working Voltage: 12V</li> </ul>
Environment	<ul style="list-style-type: none"> <li>➤ Storage Temperature: -40~70°C</li> <li>➤ Operating Temperature: -10~55°C</li> <li>➤ Relative Humidity: 5-90% ( no condensation)</li> </ul>
Warranty	2 years
Physical Characteristics	<ul style="list-style-type: none"> <li>➤ Dimension: 136×54×27mm</li> <li>➤ Weight: 0.26kg</li> <li>➤ Color: Black</li> </ul>

Maahantuonti ja tekninen tuki:

Microdata Finland Oy  
 Robert Huberin tie 2  
 01510 VANTAA

[tuki@microdata.fi](mailto:tuki@microdata.fi) / +358 9 42474920