1)Thermostat networking steps:

Press and hold the up and down keys for about 5 seconds when the thermostat is turned on. When you hear the buzzer ringing 1 sounds, Then short press the “Plus”or “Minus”button.the thermostat enters the distribution network interface. After the screen displays full display(or press the power button to exit) the thermostat has entered the networkinitialization status .When the WiFi symbol" " of the thermostat does not flash, it indicates that the connection is successful. Please note that the router or the corresponding WiFi device is turned on and within 5 meters of the thermostat.

2)Mobile phone networking steps:

Before configuring WIFI , please make sure your phone is connected to 2.4GHz WIFI.

1. Use your mobile phone to scan the QR code below to download the" Tuya Smart "app.


China

Foreign

2.0pen the "Tuya Smart " app and click "Add Device" as shown below.




3.After clicking" Small Home Appliances", select "Thermostat" as shown below.



4.Click" confirm indicator rapidly blink" as shown below.



5.After entering the WIFI password, press "Confirm" as shown below.




6.The phone enters the device search and the connection mode is as shown below.



7.The mobile phone adds the device connection successfully, click" Done" as shown below.



8.Click on the" Done" button above to enter the control interface as shown below.



3)Device sharing instructions:

1.Click" "as shown below.

2.Click"Share Device" as shown below.

3.Click" Add Sharing" as shown below.

4.After entering the account number, click" Done" as shown below.



4)Thermostat and mobile phone Exit the network:

Press and hold the up and down button for about 5 seconds while the thermostat is off. When the buzzer sounds 3 times into the distribution network interface, the screen displays full display. At this time (or press the power button to exit) the control panel has entered the network exit state (also the distribution network state).