Adopt ecological paper printing for this manual

© Weihao electronic all rights reserved

WEHO®

ZHEJIANG WEIHAO ELECTRONIC CO.,LTD.

Add: No.231–2, Weiliu Road, Yueqing Economic Development Zone,
Yueqing City, Zhejiang Province
Tel：0086–577–61777088
Fax：0086–577–61777072
E–mail: weho@chnwh.com
Http://www.wehopower.com

WEHO®

PRODUCT GUIDE

WEIHAO
SWITCHING POWER SUPPLY



LRS Series Power Supply



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-35-12	12V	3A	84%
LRS-35-24	24V	1.5A	86%
LRS-35-36	36V	1A	87%
LRS-35-48	48V	0.8A	87%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-50-12	12V	4.2A	84%
LRS-50-24	24V	2.2A	86%
LRS-50-36	36V	1.3A	87%
LRS-50-48	48V	1.1A	87%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-60-12	12V	5A	84%
LRS-60-15	15V	4A	84%
LRS-60-24	24V	2.5A	86%
LRS-60-48	48V	1.25A	87%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*97*30MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-75-12	12V	6A	86%
LRS-75-24	24V	3.2A	87%
LRS-75-36	36V	2A	88%
LRS-75-48	48V	1.6A	88%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 129*97*30MM
- Weight 0.34KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-100-12	12V	8.5A	86%
LRS-100-24	24V	4.5A	87%
LRS-100-36	36V	2.7A	88%
LRS-100-48	48V	2.3A	88%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 129*97*30MM
- Weight 0.34KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-120-12	12V	10A	86%
LRS-120-15	15V	8A	86%
LRS-120-24	24V	5A	87%
LRS-120-48	48V	2.5A	87%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -20~+70℃
- Dimension 159*97*30MM
- Weight 0.48KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-150-12	12V	12.5A	84%
LRS-150-24	24V	6.5A	86%
LRS-150-36	36V	4.1A	87%
LRS-150-48	48V	3.3A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.66KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-200-12	12V	17A	84%
LRS-200-24	24V	8.8A	86%
LRS-200-36	36V	5.5A	87%
LRS-200-48	48V	4.4A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.66KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-250-12	12V	20A	86%
LRS-250-15	15V	16A	86%
LRS-250-24	24V	10A	87%
LRS-250-48	48V	5A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-350-12	12V	29A	83%
LRS-350-15	15V	23.2A	84%
LRS-350-24	24V	14.6A	86%
LRS-350-27	27V	12.9A	87%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-350-36	36V	9.7A	87%
LRS-350-48	48V	7.3A	87%
LRS-350-60	60V	5.83A	88%
LRS-350-70	70V	5A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-400-12	12V	33A	83%
LRS-400-15	15V	26.7A	84%
LRS-400-24	24V	16.5A	85%
LRS-400-48	48V	8.3A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-500-12	12V	40A	86%
LRS-500-24	24V	20A	87%
LRS-500-36	36V	14A	88%
LRS-500-48	48V	10A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-600-12	12V	40A	83%
LRS-600-24	24V	25A	84%
LRS-600-36	36V	16.7A	85%
LRS-600-48	48V	12.5A	86%

S Series Single Output Power Supply



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 98*97*35MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-15-5	5V	3A	65%
S-15-12	12V	1.3A	68%
S-15-24	24V	0.7A	72%
S-15-48	48V	0.3A	72%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 98*97*35MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-25-5	5V	5A	65%
S-25-12	12V	2.1A	68%
S-25-24	24V	1.1A	72%
S-25-48	48V	0.52A	72%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 129*98*38MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-35-5	5V	7A	70%
S-35-12	12V	3A	76%
S-35-24	24V	1.5A	78%
S-35-48	48V	0.72A	78%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-50-5	5V	10A	71%
S-50-12	12V	4.2A	78%
S-50-24	24V	2.1A	82%
S-50-48	48V	1.04A	82%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-60-5	5V	12A	72%
S-60-12	12V	5A	78%
S-60-24	24V	2.5A	82%
S-60-48	48V	1.25A	82%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-75-12	12V	6A	78%
S-75-15	15V	5A	79%
S-75-24	24V	3.2A	82%
S-75-48	48V	1.5A	83%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*98*38MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-100-5	5V	20A	78%
S-100-12	12V	8.5A	81%
S-100-24	24V	4.5A	84%
S-100-48	48V	2.1A	84%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*98*38MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-120-12	12V	10A	81%
S-120-15	15V	8A	82%
S-120-24	24V	5A	84%
S-120-48	48V	2.5A	84%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*98*38MM
- Weight 0.7KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-145-5	5V	25A	75%
S-145-12	12V	12A	80%
S-145-24	24V	6A	83%
S-145-48	48V	3A	83%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*110*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-150-5	5V	30A	78%
S-150-12	12V	12.5A	82%
S-150-24	24V	6.5A	85%
S-150-48	48V	3.13A	87%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*110*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-200-5	5V	40A	79%
S-200-12	12V	16.5A	82%
S-200-24	24V	8.5A	83%
S-200-48	48V	4.2A	86%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-201-5	5V	40A	74%
S-201-12	12V	16.5A	80%
S-201-24	24V	8.5A	83%
S-201-48	48V	4.2A	84%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-250-12	12V	20A	79%
S-250-15	15V	16A	79%
S-250-24	24V	10A	81%
S-250-48	48V	5A	84%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-320-12	12V	26.6A	83%
S-320-24	24V	13.3A	85%
S-320-36	36V	8.9A	85%
S-320-48	48V	6.6A	86%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-350-5	5V	50A	73%
S-350-12	12V	29A	83%
S-350-24	24V	14.6A	85%
S-350-48	48V	7.3A	86%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-400-5	5V	60A	73%
S-400-12	12V	33A	82%
S-400-24	24V	16.5A	83%
S-400-48	48V	8.3A	85%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 238*124*65MM
- Weight 1.35KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-500-12	12V	40A	83%
S-500-24	24V	20A	85%
S-500-36	36V	14A	86%
S-500-48	48V	10A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 238*124*65MM
- Weight 1.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-600-12	12V	50A	83%
S-600-24	24V	25A	85%
S-600-36	36V	16.7A	86%
S-600-48	48V	12.5A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-800-12	12V	66A	80%
S-800-24	24V	33A	85%
S-800-36	36V	22A	85%
S-800-48	48V	17A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-1000-12	12V	80A	80%
S-1000-24	24V	42A	85%
S-1000-36	36V	28A	85%
S-1000-48	48V	21A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-1200-12	12V	100A	80%
S-1200-24	24V	50A	82%
S-1200-36	36V	33A	84%
S-1200-48	48V	25A	85%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-1500-12	12V	125A	80%
S-1500-24	24V	62.5A	81%
S-1500-36	36V	41A	83%
S-1500-48	48V	32A	84%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-2000-24	24V	83.3A	85%
S-2000-36	36V	55.5A	85%
S-2000-48	48V	41.6A	87%
S-2000-60	60V	33.4A	88%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-2400-24	24V	100A	85%
S-2400-36	36V	66.6A	85%
S-2400-48	48V	50A	87%
S-2400-60	60V	40A	88%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-3000-24	24V	125A	85%
S-3000-36	36V	83.3A	85%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-3000-48	48V	62.5A	87%
S-3000-60	60V	50A	88%

SCN Series Parallel Power Supply



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.65KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-800-12	12V	66A	80%
SCN-800-24	24V	33A	85%
SCN-800-36	36V	22A	85%
SCN-800-48	48V	17A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*68MM
- Weight 2.65KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1000-12	12V	80A	80%
SCN-1000-24	24V	42A	85%
SCN-1000-36	36V	28A	86%
SCN-1000-48	48V	21A	87%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1200-12	12V	100A	80%
SCN-1200-24	24V	50A	82%
SCN-1200-36	36V	33A	84%
SSN-1200-48	48V	25A	85%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 291*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1500-12	12V	125A	80%
SCN-1500-24	24V	62.5A	81%
SCN-1500-36	36V	41A	83%
SCN-1500-48	48V	32A	84%

MS Series Mini Type Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 78*48*21MM
- Weight 0.15KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MSF-10-5	5V	2A	71%
MSF-10-12	12V	1A	73%
MSF-10-15	15V	0.8A	74%
MSF-10-24	24V	0.5A	75%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 84*58*38MM
- Weight 0.21KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-15-5	5V	3A	68%
MS-15-12	12V	1.3A	71%
MS-15-24	24V	0.7A	75%
MS-15-48	48V	0.3A	75%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 97*58*25MM
- Weight 0.19KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MSF-20-5	5V	4A	72%
MSF-20-12	12V	2A	74%
MSF-20-15	24V	1.6A	74%
MSF-20-24	48V	1A	76%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 84*58*38MM
- Weight 0.21KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-25-5	5V	5A	70%
MS-25-12	12V	2.1A	75%
MS-25-24	24V	1.1A	78%
MS-25-48	48V	0.52A	78%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 84*58*38MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-35-5	5V	6A	77%
MS-35-12	12V	3A	83%
MS-35-24	24V	1.5A	84%
MS-35-48	48V	0.73A	84%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 111*78*36MM
- Weight 0.27KGS
- 2 Years Warranty


Model	DC output	Current	Efficiency
MS-50-5	5V	10A	80%
MS-50-12	12V	4.2A	82%
MS-50-24	24V	2.1A	84%
MS-50-48	48V	1.04A	84%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 111*78*36MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-60-12	12V	5A	82%
MS-60-15	15V	4A	83%
MS-60-24	24V	2.5A	84%
MS-60-48	48V	1.25A	84%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 111*78*36MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-75-12	12V	6A	82%
MS-75-15	15V	5A	83%
MS-75-24	24V	3A	84%
MS-75-48	48V	1.56A	84%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-100-5	5V	20A	80%
MS-100-12	12V	8.5A	83%
MS-100-24	24V	4.5A	86%
MS-100-48	48V	2.08A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-120-12	12V	10A	81%
MS-120-24	24V	5A	84%
MS-120-36	36V	3.3A	84%
MS-120-48	48V	2.5A	84%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-150-12	12V	12.5A	83%
MS-150-15	15V	10A	84%
MS-150-24	24V	6.5A	86%
MS-150-48	48V	3.13A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-500-12	12V	40A	86%
MS-500-24	24V	20A	87%
MS-500-36	36V	14A	88%
MS-500-48	48V	10A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-600-12	12V	40A	83%
MS-600-24	24V	25A	84%
MS-600-36	36V	16.7A	85%
MS-600-48	48V	12.5A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 238*124*65MM
- Weight 1.35KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-1000-24	24V	40A	87%
MS-1000-36	36V	28A	88%
MS-1000-48	48V	21A	89%
MS-1000-60	60V	16.7A	89%

NES Series Power Supply



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 98*97*35MM
- Weight 0.36KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-35-5	5V	7A	78%
NES-35-12	12V	3A	81%
NES-35-24	24V	1.5A	85%
NES-35-48	48V	0.73A	85%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 129*98*38MM
- Weight 0.41KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-50-5	5V	10A	79%
NES-50-12	12V	4.2A	82%
NES-50-24	24V	2.2A	86%
NES-50-48	48V	1.04A	86%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.52KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-75-5	5V	14A	77%
NES-75-12	12V	6.2A	82%
NES-75-24	24V	3.2A	86%
NES-75-48	48V	1.56A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-100-5	5V	20A	80%
NES-100-12	12V	8.5A	83%
NES-100-24	24V	4.5A	86%
NES-100-48	48V	2.3A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*98*38MM
- Weight 0.7KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-150-5	5V	30A	78%
NES-150-12	12V	12.5A	83%
NES-150-24	24V	6.5A	84%
NES-150-48	48V	3.3A	86%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 0.93KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-200-5	5V	40A	78%
NES-200-12	12V	17A	83%
NES-200-24	24V	8.8A	86%
NES-200-48	48V	4.4A	86%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-350-5	5V	60A	78%
NES-350-12	12V	29A	83%
NES-350-15	15V	23.3A	84%
NES-350-24	24V	14.6A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-350-27	27V	12.9A	87%
NES-350-36	36V	9.7A	87%
NES-350-48	48V	7.3A	87%
NES-350-60	60V	5.83A	88%

D Series Dual Ouput Power Supply



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 129*98*38MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
D-30A	5V,12V	4A,1A	72%
D-30B	5V,24V	2A,1A	74%
D-30C	12V,-12V	1.5A,1A	74%
D-30F	12V,24V	1A,1A	75%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
D-50A	5V,12V	6A,2A	73%
D-50B	5V,24V	6A,1A	73%
D-50C	12V,-12V	2A,2A	75%
D-50F	12V,24V	2A,1A	76%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
D-60A	5V,12V	4A,3A	73%
D-60B	5V,24V	3A,1.8A	76%
D-60C	12V,-12V	2.5A,2.5A	75%
D-60F	12V,24V	2A,1.5A	76%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*110*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
D-120A	5V,12V	12A,5A	76%
D-120B	5V,24V	6A,4A	78%
D-120C	12V,-12V	5A,5A	80%
D-120F	12V,24V	5A,2.5A	80%

T Series Triple Output Power Supply



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 129*98*38MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
T-30A	5V,12V,-5V	3A,1A,0.5A	70%
T-30B	5V,12V,-12V	3A,1A,0.5A	72%
T-30C	5V,15V,-15V	3A,0.5A,0.5A	72%
T-30D	5V,12V,24V	3A,0.5A,0.5A	72%




Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
T-50A	5V,12V,-5V	7A,1A,1A	66%
T-50B	5V,12V,-12V	5A,1A,1A	69%
T-50C	5V,15V,-15V	4A,1A,1A	71%
T-50D	5V,12V,24V	3A,1A,1A	72%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
T-60A	5V,12V,-5V	5A,2.5A,0.5A	72%
T-60B	5V,12V,-12V	5A,2.5A,0.5A	72%
T-60C	5V,15V,-15V	5A,2A,0.5A	72%
T-60D	5V,12V,24V	5A,2.5A,0.5A	72%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*110*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
T-120A	5V,12V,-5V	11A,5A,1A	77%
T-120B	5V,12V,-12V	11A,4.5A,1A	77%
T-120C	5V,15V,-15V	10A,3.5A,1A	76%
T-120D	5V,12V,24V	8A,2.5A,2A	80%

Q Series Qual Series Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 159*98*38MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
Q-60B	5V,12V,-5V,-12V	5.5A,2A,0.5A,0.5A	70%
Q-60C	5V,15V,-5V,-15V	5.5A,1.5A,0.5A,0.5A	72%
Q-60D	5V,12V,24V,-12V	4A,1A,1A,0.5A	75%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -10~+50℃
- Dimension 199*110*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
Q-120B	5V,12V,-5V,-12V	11A,4A,1A,1A	77%
Q-120C	5V,15V,-5V,-15V	10A,3.5A,1A,1A	76%
Q-120D	5V,12V,24V,-12V	8A,2A,2A,1A	80%

SP Series Single Output With PFC Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 179*99*45MM
- Weight 0.66KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-100-5	5V	20A	76%
SP-100-12	12V	8.5A	80%
SP-100-24	24V	4.2A	84%
SP-100-48	48V	2.1A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 199*99*50MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-150-5	5V	30A	75%
SP-150-12	12V	12.5A	80%
SP-150-24	24V	6.3A	83%
SP-150-48	48V	3.2A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 199*99*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-200-5	5V	40A	75%
SP-200-12	12V	16.7A	79%
SP-200-24	24V	8.4A	83%
SP-200-48	48V	4.2A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 215*115*50MM
- Weight 1.1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-320-5	5V	55A	79%
SP-320-12	12V	25A	84%
SP-320-24	24V	13A	85%
SP-320-48	48V	6.7A	88%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 185*120*93MM
- Weight 1.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-500-12	12V	40A	84%
SP-500-24	24V	20A	85.5%
SP-500-48	48V	10A	87%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 185*120*93MM
- Weight 2KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-600-12	12V	50A	84%
SP-600-24	24V	25A	85.5%
SP-600-48	48V	12.5A	87%

SD Series DC Power Supply



Features :
- DC Input A:9.2~18V/ B:18~36V/C:36~72V
- Working Temp. -10~+60℃
- Dimension 78*51*28MM
- Weight 0.18KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-15□-05	5V	3A	76%
SD-15□-12	12V	1.25A	76%
SD-15□-24	24V	0.63A	77%



Features :
- DC Input A:9.2~18V/ B:19~36V/C:36~72V
- Working Temp. -10~+60℃
- Dimension 99*97*36MM
- Weight 0.38KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-25□-05	5V	5A	72%
SD-25□-12	12V	2.1A	75%
SD-25□-24	24V	1.1A	78%



Features :
- DC Input A:9.2~18V/ B:19~36V/C:36~72V
- Working Temp. -10~+60℃
- Dimension 159*97*38MM
- Weight 0.48KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-50□-05	5V	10A	73%
SD-50□-12	12V	4.2A	75%
SD-50□-24	24V	2.1A	80%



Features :
- DC Input A:19~36V/B:36~72V /C:72~144V or 85~132VAC
- Working Temp. -10~+60℃
- Dimension 199*98*38MM
- Weight 0.65KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-100□-05	5V	20A	75%
SD-100□-12	12V	8.5A	77%
SD-100□-24	24V	4.2A	81%



Features :
- DC Input B:19~36VDC/ C:36~72VDC/D:72~144VDC
- Working Temp. -10~+60℃
- Dimension 199*110*50MM
- Weight 0.86KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-150□-12	12V	12.5A	75%
SD-150□-24	24V	6.3A	77%



Features :
- DC Input B:19~36VDC/ C:36~72VDC/D:72~144VDC
- Working Temp. -20~+60℃
- Dimension 215*115*50MM
- Weight 1.1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-200□-05	5V	34A	79%
SD-200□-12	12V	16.7A	82%
SD-200□-24	24V	8.4A	85%
SD-200□-48	48V	4.2A	86%

AD Series Power Supply with Battery Charging Function(UPS)



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 159*98*38MM
- Weight 0.49KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
AD-55A	13.8V,13.4V	3.5A,0.23A	71%
AD-55B	27.6V,26.5V	1.8A,0.16A	74%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+60℃
- Dimension 199*110*50MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
AD-155A	13.8V,13.3V	9.5A,0.5A	80%
AD-155B	27.6V,27.1V	4.5A,0.5A	84%
AD-155C	54V,53.5V	2.3A,0.2A	84%

SC Series Power Supply with Battery Charging Function(UPS)



Features :
- AC Input Full Range 85~264V/UPS
- Battery Protection At Low Voltage
- Working Temp. -10~+50℃
- Dimension 111*78*36MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-35-12	CH1:13.8V CH2:13.4V	2A,0.5A	81%
SC-35-24	CH1:27.6V CH2:26.5V	1A,0.3A	83%



Features :
- AC Input Full Range 85~264V/UPS
- Battery Protection At Low Voltage
- Working Temp. -10~+60℃
- Dimension 129*98*38MM
- Weight 0.52KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-60-12	CH1:13.8V CH2:13.4V	4A,0.35A	81%
SC-60-24	CH1:27.6V CH2:26.5V	2A,0.25A	83%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Battery Protection At Low Voltage
- Working Temp. -10~+60℃
- Dimension 159*98*38MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-120-12	CH1:13.8V CH2:13.4V	8A,0.5A	84%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Battery Protection At Low Voltage
- Working Temp. -10~+60℃
- Dimension 159*98*38MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-120-24	CH1:27.6V CH2:26.5V	4A,0.3A	86%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Battery Protection At Low Voltage
- Working Temp. -10~+50℃
- Dimension 199*98*38MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-180-12	CH1:12V CH2:13.8V	13.5A,1.5A	85%
SC-180-24	CH1:24V CH2:27.6V	6.5A,1A	87%



Features :
- AC Input 90~132V/180~264V By Switch/47~63Hz
- Battery Protection At Low Voltage
- Working Temp. -10~+50℃
- Dimension 215*115*50MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-350-12	CH1:13.8V CH2:13.8V	21A,5A	84%
SC-350-24	CH1:27.6V CH2:27.6V	9A,5A	86%

NDR Series Din Rail Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 32*125.2*102MM
- Weight 0.51KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NDR-75-12	12V	6.3A	85%
NDR-75-24	24V	3.2A	88%
NDR-75-36	36V	2.1A	89%
NDR-75-48	48V	1.6A	89%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*125.2*113.5MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NDR-120-12	12V	10A	85%
NDR-120-24	24V	5A	88%
NDR-120-36	36V	3.4A	89%
NDR-120-48	48V	2.5A	89%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 63*125.2*113.5MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NDR-240-24	24V	10A	88%
NDR-240-36	36V	6.6A	89%
NDR-240-48	48V	5A	89%
NDR-240-60	60V	4A	90%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 85.5*125.2*128.5MM
- Weight 1.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NDR-480-24	24V	20A	92%
NDR-480-36	36V	13.3A	92%
NDR-480-48	48V	10A	92%
NDR-480-60	60V	8A	92%

EDR Series Din Rail Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 32*125.2*102MM
- Weight 0.51KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
EDR-75-12	12V	6.3A	85%
EDR-75-24	24V	3.2A	88%
EDR-75-36	36V	2.1A	89%
EDR-75-48	48V	1.6A	89%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*125.2*113.5MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
EDR-120-12	12V	10A	85%
EDR-120-24	24V	5A	87%
EDR-120-36	36V	3.4A	87%
EDR-120-48	48V	2.5A	88%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*125.2*113.5MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
EDR-150-24	24V	6.5A	85%
EDR-150-36	36V	4.2A	86%
EDR-150-48	48V	3.2A	87%
EDR-150-60	60V	2.5A	87%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 63*125.2*113.5MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
EDR-240-24	24V	10A	87%
EDR-240-36	36V	6.6A	87%
EDR-240-48	48V	5A	88%
EDR-240-60	60V	4A	88%

DR Series Din Rail Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 78*93*56MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-30-5	5V	3A	74%
DR-30-12	12V	2A	81%
DR-30-24	24V	1.5A	83%
DR-30-48	48V	0.62A	83%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 78*93*56MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-45-5	5V	5A	72%
DR-45-12	12V	3.5A	77%
DR-45-24	24V	2A	80%
DR-45-48	48V	0.93A	80%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 78*93*56MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-60-5	5V	6.5A	76%
DR-60-12	12V	4.5A	82%
DR-60-24	24V	2.5A	84%
DR-60-48	48V	1.25A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 55.5*125.5*100MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-75-12	12V	6.3A	76%
DR-75-15	15V	5A	80%
DR-75-24	24V	3.2A	80%
DR-75-48	48V	1.6A	81%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 65.5*125.5*100MM
- Weight 0.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-120-12	12V	10A	80%
DR-120-15	15V	8A	81%
DR-120-24	24V	5A	84%
DR-120-48	48V	2.5A	85%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 125.5*125.5*100MM
- Weight 1.2KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-240-12	12V	20A	83%
DRP-240-24	24V	10A	84%
DRP-240-36	36V	6.66A	85%
DRP-240-48	48V	5A	85%

MDR Series Mini Din Rail Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 22.5*90*100MM
- Weight 0.17KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-10-5	5V	2A	77%
MDR-10-12	12V	0.84A	81%
MDR-10-15	15V	0.6A	82%
MDR-10-24	24V	0.42A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 22.5*90*100MM
- Weight 0.19KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-20-5	5V	3A	76%
MDR-20-12	12V	1.67A	80%
MDR-20-15	15V	1.34A	81%
MDR-20-24	24V	1A	84%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*90*100MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-40-5	5V	6A	78%
MDR-40-12	12V	3.33A	86%
MDR-40-24	24V	1.7A	88%
MDR-40-48	48V	0.83A	88%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*90*100MM
- Weight 0.33KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-60-5	5V	10A	76%
MDR-60-12	12V	5A	84%
MDR-60-24	24V	2.5A	86%
MDR-60-48	48V	1.25A	86%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 55*90*100MM
- Weight 0.42KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-100-12	12V	7.5A	83%
MDR-100-15	15V	6.6A	83%
MDR-100-24	24V	4.16A	86%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 55*90*100MM
- Weight 0.42KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-100-27	27V	3.7A	86%
MDR-100-36	36V	2.7A	86%
MDR-100-48	48V	2A	87%

HDR Series Din Rail Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 17.5*90*54.5MM
- Weight 0.08KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
HDR-15-5	5V	2.4A	78%
HDR-15-12	12V	1.25A	83%
HDR-15-24	24V	0.63A	84%
HDR-15-48	48V	0.32A	85%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 35*90*54.5MM
- Weight 0.12KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
HDR-30-5	5V	3A	80%
HDR-30-12	12V	2A	86%
HDR-30-24	24V	1.5A	87%
HDR-30-48	48V	0.75A	87%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 52.5*90*54.5MM
- Weight 0.19KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
HDR-60-5	5V	6.5A	82%
HDR-60-12	12V	4.5A	85%
HDR-60-24	24V	2.5A	88%
HDR-60-48	48V	1.25A	88%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 70*90*54.5MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
HDR-100-12	12V	7.5A	86%
HDR-100-15	15V	6.5A	86%
HDR-100-24	24V	4.2A	88%
HDR-100-48	48V	2.1A	88%

XLG Series Waterproof Power Supply



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 182*30*20MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-25-12	12V	2A	86.5%
XLG-25-24	24V	1A	87.5%
XLG-25-36	36V	0.7A	87.5%
XLG-25-48	48V	0.5A	88.5%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 182*30*20MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-35-12	12V	3A	86.5%
XLG-35-24	24V	1.5A	87.5%
XLG-35-36	36V	1A	87.5%
XLG-35-48	48V	0.75A	88.5%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 170*49*34MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-50-12	12V	4.2A	86.5%
XLG-50-24	24V	2.1A	87.5%
XLG-50-36	36V	1.4A	87.5%
XLG-50-48	48V	1.05A	88.5%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 170*49*34MM
- Weight 0.45KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-60-12	12V	5A	87.5%
XLG-60-24	24V	2.5A	88.5%
XLG-60-36	36V	1.7A	89.5%
XLG-60-48	48V	1.25A	90%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 170*49*34MM
- Weight 0.45KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-75-12	12V	6A	87.5%
XLG-75-24	24V	3A	88.5%
XLG-75-36	36V	2A	89.5%
XLG-75-48	48V	1.5A	90%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 190*49*34MM
- Weight 0.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-100-12	12V	8.3A	87.5%
XLG-100-24	24V	4.2A	89%
XLG-100-36	36V	2.8A	90%
XLG-100-48	48V	2.1A	91%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 190*49*34MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-120-12	12V	10A	87.5%
XLG-120-24	24V	5A	89%
XLG-120-36	36V	3.3A	90%
XLG-120-48	48V	2.5A	91%



Features :
- Input Full Range 95~264VAC/135~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 190*49*34MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-150-12	12V	12.5A	90%
XLG-150-24	24V	6.3A	91%
XLG-150-36	36V	4.2A	92%
XLG-150-48	48V	3.2A	93%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 205*69*43MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-200-12	12V	16.5A	90%
XLG-200-24	24V	8.3A	92%
XLG-200-36	36V	5.6A	93%
XLG-200-48	48V	4.2A	94%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 205*69*43MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-250-12	12V	16.5A	91%
XLG-250-24	24V	10A	92%
XLG-250-36	36V	7A	92.5%
XLG-250-48	48V	5.2A	93%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 240*69*43MM
- Weight 0.95KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-350-12	12V	25A	91.3%
XLG-350-24	24V	14.5A	92%
XLG-350-36	36V	10A	93%
XLG-350-48	48V	7.3A	94%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 240*69*43MM
- Weight 1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-400-24	24V	16.5A	92.3%
XLG-400-36	36V	11A	93%
XLG-400-45	45V	8.8A	93.5%
XLG-400-48	48V	8.3A	94%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 205*120*56MM
- Weight 1.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-500-24	24V	20A	92%
XLG-500-36	36V	13.5A	92.5%
XLG-500-48	48V	10.5A	93.5%
XLG-500-60	60V	8.3A	94.5%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 235*120*56MM
- Weight 1.95KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-650-24	24V	25A	91.5%
XLG-650-36	36V	18A	92.5%
XLG-650-48	48V	13.5A	93%
XLG-650-60	60V	10.8A	94%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 265*120*56MM
- Weight 2.1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-800-24	24V	27A	92.5%
XLG-800-36	36V	22A	93%
XLG-800-48	48V	16.5A	93.5%
XLG-800-60	60V	13.5A	94%



Features :
- AC Input 90-132V or 180-264V /235~373VDC 47~63Hz
- Working Temp. -20~+60℃
- Dimension 340*120*56MM
- Weight 3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
XLG-1200-48	48V	25A	93.5%

LPV Series Waterproof Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 182*30*20MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-20-12	12V	1.67A	78%
LPV-20-24	24V	0.84A	80%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 222*30*20MM
- Weight 0.25KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-30-12	12V	2.5A	78%
LPV-30-24	24V	1.25A	80%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 190*47*38MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-50-12	12V	4.2A	81%
LPV-50-24	24V	2.1A	83%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 180*68*50MM
- Weight 0.78KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-60-12	12V	5A	81%
LPV-60-24	24V	2.5A	83%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 185*69*43MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-12	12V	8.5A	81%
LPV-100-24	24V	4.5A	83%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 245*69*43MM
- Weight 1.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-150-12	12V	12.5A	81%
LPV-150-24	24V	6.5A	83%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 245*69*43MM
- Weight 1.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-200-12	12V	16.5A	81%
LPV-200-24	24V	8.3A	83%



Features :
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 230*122*60MM
- Weight 2.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-250-12	12V	20A	81%
LPV-250-24	24V	10A	83%

WL Series Ultra Thin LED Power Supply



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 116*35*22MM
- Weight 0.085KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-36-12	12V	3A	86%
WL-36-24	24V	1.5A	86%
WL-36-36	36V	1A	89%
WL-36-48	48V	0.75A	90%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 142*35*30MM
- Weight 0.11KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-60-12	12V	5A	88%
WL-60-24	24V	2.5A	89%
WL-60-36	36V	1.67A	89%
WL-60-48	48V	2.5A	90%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 138*50*22MM
- Weight 0.16KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-100-12	12V	8.3A	86%
WL-100-24	24V	4.2A	89%
WL-100-36	36V	2.8A	89%
WL-100-48	48V	2.1A	90%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 178*50*22MM
- Weight 0.21KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-150-12	12V	12.5A	87%
WL-150-24	24V	6.2A	89%
WL-150-36	36V	4.2A	89%
WL-150-48	48V	3.2A	90%



Features :
- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 178*50*22MM
- Weight 0.23KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-200-12	12V	16.6A	87%
WL-200-24	24V	8.3A	89%
WL-200-36	36V	5.6A	89%
WL-200-48	48V	4.2A	90%



Features :
- AC Input 90-132V or 180-264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 187*60*28MM
- Weight 0.35KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-300-12	12V	25A	88%
WL-300-24	24V	12.5A	89%
WL-300-36	36V	8.3A	89%
WL-300-48	48V	6.25A	90%



Features :
- AC Input 90-132V or 180-264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 220*60*28MM
- Weight 0.45KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-400-12	12V	33.3A	88%
WL-400-24	24V	16.6A	89%



Features :
- AC Input 90-132V or 180-264V /47~63Hz
- Working Temp. -10~+50℃
- Dimension 220*60*28MM
- Weight 0.45KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WL-400-36	36V	11.1A	89%
WL-400-48	48V	8.3A	90%

LPV Series Plastic Waterproof Power Supply



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 118*35*26MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-10-5E	5V	2A	77%
LPV-10-12E	12V	0.8A	81%
LPV-10-15E	15V	0.6A	83%
LPV-10-24E	24V	0.4A	83%



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 118*35*26MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-20-5E	5V	3A	77%
LPV-20-12E	12V	1.67A	81%
LPV-20-15E	15V	1.33A	83%
LPV-20-24E	24V	0.84A	83%



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 148*40*30MM
- Weight 0.34KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-40-5E	5V	6A	77%
LPV-40-12E	12V	3.3A	84%
LPV-40-15E	15V	2.6A	84%
LPV-40-24E	24V	1.6A	85%
LPV-40-36E	36V	1A	85%



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 162.5*42.5*32MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-60-5E	5V	8A	76%
LPV-60-12E	12V	5A	83%
LPV-60-15E	15V	4A	83%
LPV-60-24E	24V	2.5A	86%
LPV-60-36E	36V	1.67A	86%



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 190*52*37MM
- Weight 0.63KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-5E	5V	12A	80%
LPV-100-12E	12V	8.5A	85%
LPV-100-15E	15V	6.7A	87%



Features :
- Input Full Range 90~264VAC/47~63Hz
- Working Temp. -20~+50℃
- Dimension 190*52*37MM
- Weight 0.63KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-24E	24V	4.2A	88%
LPV-100-36E	36V	2.8A	88%
LPV-100-48E	48V	2.1A	89%

ERP Series Rain Proof Power Supply



Features :
- Input Full Range 85~264VAC/254~370VDC 47~63Hz
- Working Temp. -30~+60℃
- Dimension 220.4*130*48MM
- Weight 1.1KGS
- 2 Years Warranty


Model	DC output	Current	Efficiency
ERP-350-12	12V	26.7A	85%
ERP-350-24	24V	14.6A	87%
ERP-350-36	36V	9.7A	89%
ERP-350-48	48V	7.3A	89%



Features :
- Input Full Range 85~264VAC/254~370VDC 47~63Hz
- Working Temp. -30~+60℃
- Dimension 220.4*130*48MM
- Weight 1.2KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
ERP-400-12	12V	30A	87%
ERP-400-24	24V	16.7A	90%
ERP-400-36	36V	11.1A	89%
ERP-400-48	48V	8.3A	89%

WH Series DC DC Converter



Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 66*58*23MM
- Weight 0.11KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2403	24V	3A	93%



Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2405	24V	5A	93%



Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2410	24V	10A	94%



Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2415	24V	15A	93%




Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 100*80*38MM
- Weight 0.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2420	24V	20A	93%




Features :
- DC Input 10~16V
- Working Temp. -10~+55℃
- Dimension 150*127*63MM
- Weight 1.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B2430	24V	30A	94%



Features :
- DC Input 18~32V
- Working Temp. -10~+55℃
- Dimension 66*58*23MM
- Weight 0.11KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1205	12V	5A	95%



Features :
- DC Input 18~32V
- Working Temp. -10~+55℃
- Dimension 66*58*23MM
- Weight 0.11KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1210	12V	10A	96%



Features :
- DC Input 18~32V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1215	12V	15A	95%



Features :
- DC Input 18~32V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1220	12V	20A	95%



Features :
- DC Input 18~32V
- Working Temp. -10~+55℃
- Dimension 74*74*32MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1230	12V	30A	95%